













UNDER
260000

M2 106
PLUS



ULTRA LOW
NOISE FOOT PEDAL
200-1117

WARNING
READ & FOLLOW
INSTRUCTIONS



DANGER

CAUTION: The engine is hot. Do not touch. Do not start the engine until the engine is cooled. Do not start the engine until the engine is cooled.



Automatic Fan
Keep hands clear
when angles in
turning.
Fan starts to stop
by itself.





IMPORTANT


IMPORTANT

- Set to Cold Full. Wait 2 minutes and top up.
- Release until vent remains stable at Cold Full.
- If required, vent TransAire cooler and top up.
- Cold Full.
- Run engine until thermostat opens.
- Shut down and top up to Cold Full.
- Check Oil.

ATTENTI

ATTENTION:
Factory Filled with N
FREE OAT Extender
Constant (ELC)
Est. Service: Use Only
ADDITIONAL FREE OAT EL
Constant, Do Not Add
Conventional Constatants or
SCAs
Consulting Consultant:
See Engine Operator's Manual
for details.

68



Out: 01/01/1900

RIER INC

rough

REIGHTLINER M2P

VIN 3ALACWF080VT0042

CUSTOMER IS BILLABLE



SMART SOURCE
MEBANE, NC
USDOT 142801
MC 539751

GVW















SMARTCOURIER
SMART COURIER, INC. NC.
MERANE, NC.

USDOT 1428018
MC 539751



GVW UNDER 26000





VT5682



MM106 Bld dt:2024-04-02 Seq#:193











